

Schoch Harley-Davidson

Service Department

V-Rod Models

Vehicle Maintenance Schedule

Item Serviced	Procedure	1,000						
		5,000	10,000	15,000	20,000	25,000	30,000	DONE
Engine Oil & Filter	Replace or Inspect Level	R	R	R	R	R	R	
Oil Lines & Brake Lines	Inspect for leaks	I	I	I	I	I	I	
Air Cleaner	Inspect and Clean	I	R	I	R	I	R	
Tires	Inspect Tread, Check Pressure	I	I	I	I	I	I	
Clutch Fluid	Check Level and Condition	I	R	I	R	I	R	
Rear Belt and Sprockets	Inspect, Adjust Belt	I/A	I/A	I/A	I/A	I/A	I/A	
Throttle Cables	Adjust and Lubricate	A/L	A/L	A/L	A/L	A/L	A/L	
Clutch and Brake Levers	Lubricate	L	L	L	L	L	L	
Kick Stand	Adjust and lubricate	L	L	L	L	L	L	
Brake Fluids	Check Levels and Condition	I	R	I	R	I	R	
Brake Pads and Discs	Inspect for Wear	I	I	I	I	I	I	
Brake Components: Caliper Pins, Boots, Bushings	Inspect	I	I	I	I	I	I	
Spark Plugs	Inspect or Replace	I	R	I	R	I	R	
Front Fork Oil	Replace at 20K				R			
Steering Head Bearings -	Adjust and Lubricate	A/L	A/L	A/L	A/L	A/L	A/L	
Rear Fork Bearings	Repack							
Valve Lash	Adjust Every 15K			A			A	
Cooling System	Inspect and Check: Clamps for Tightness and Coolant Freeze Point	I	I	I	I	I	I	
Coolant	Inspect or Replace						R	
Radiator	Inspect and Clean	I	I	I	I	I	I	
Exhaust System	Check all Fasteners	C	C	C	C	C	C	
Seat Latch	Lubricate	C/L	C/L	C/L	C/L	C/L	C/L	
Electrical Equipment	Check Operaton	C	C	C	C	C	C	
Electrical Switches	Check Operation	C	C	C	C	C	C	
Electrical Diagnostic Check	Digital Technician Computer		C		C		C	
All EFI VEHICLES WILL RECEIVE A PRINTOUT USING OUR DIGITAL TECHNICIAN COMPUTER VERIFYING PROPER OPERATION AT 10Ks								
Critical Fasteners	Check Tightness	C	C	C	C	C	C	
Battery	Verify Charging and Connections	V	V	V	V	V	V	
Road Test	Verify Operation of All Components and System Functions	V	V	V	V	V	V	
Wash	Hot & Soapy with Air Blow Dry	W	W	W	W	W	W	

R = Replace

I = Inspect

A = Adjust

L = Lubricate

D=Disassemble

C=Check

V = Verify

W = Wash

Was Your Service Professional